

[54] **PEDAL OPERATED MOWER**

[76] Inventor: Deanna F. Porath, P.O. Box 7464,
Montgomery, Ala. 36107

[21] Appl. No.: 393,408

[22] Filed: Jun. 29, 1982

[51] Int. Cl.³ A01D 53/02

[52] U.S. Cl. 56/249; 56/2

[58] Field of Search 56/249, 2, 13.5;
280/261

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|-----------|---------|----------|---------|
| 613,834 | 11/1898 | Burnet | 56/249 |
| 1,250,665 | 12/1917 | Rossi | 280/261 |
| 1,713,396 | 5/1929 | Rountree | 56/249 |
| 2,715,810 | 8/1955 | Beneke | 56/249 |
| 4,341,058 | 7/1982 | Chun | 56/2 |

FOREIGN PATENT DOCUMENTS

| | | | |
|--------|--------|-----------|--------|
| 157867 | 7/1954 | Australia | 56/249 |
|--------|--------|-----------|--------|

113429 12/1968 Norway 56/249

Primary Examiner—J. N. Eskovitz

Attorney, Agent, or Firm—Harvey B. Jacobson

[57] **ABSTRACT**

A tricycle frame providing basic support for the pedal operated mower, pedals turning a forward sprocket for providing locomotion, the locomotion communicating by a chain to turn a rear sprocket mounted on a shaft having a set of split cutting blades peripherally disposed about the cutting shaft for turning the shaft and cutting blades, and gear means connecting the cutter shaft with rear wheels of the tricycle frame and resulting in the locomotion thereof. A protective shield is mounted on the tricycle frame to protect the operator from debris thrown up during the course of mowing, and also a set of goose neck handle bars, an appropriate sized front wheel and a large triangular padded seat are also provided in the combination.

8 Claims, 3 Drawing Figures

